


# DIN 6799

## Arandela seguridad

para ejes



d2	para Ø	d3	s	a
1,2	1,4 - 2,0	3,25	0,30	1,01
1,5	2,0 - 2,5	4,25	0,40	1,28
1,9	2,5 - 3,0	4,80	0,50	1,61
2,3	3,0 - 4,0	6,30	0,60	1,94
3,2	4,0 - 5,0	7,30	0,60	2,70
4,0	5,0 - 7,0	9,30	0,70	3,34
5,0	6,0 - 8,0	11,30	0,70	4,11
6,0	7,0 - 9,0	12,30	0,70	5,26
7,0	8,0 - 11,0	14,30	0,90	5,84
8,0	9,0 - 12,0	16,30	1,00	6,52
9,0	10,0 - 14,0	18,80	1,10	7,63
10,0	11,0 - 15,0	20,40	1,20	8,32
12,0	13,0 - 18,0	23,40	1,30	10,45
15,0	16,0 - 24,0	29,40	1,50	12,61
19,0	20,0 - 31,0	37,60	1,75	15,92
24,0	25,0 - 38,0	44,60	2,00	21,88

Grado	UV
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	500
1.4122	100
1.4122	100
1.4122	50
1.4122	50
1.4122	50

■ A1 / ▲ A2 / ● A4 | UV: Unidad de venta | Todas las medidas en mm | Otras dimensiones bajo pedido

Ejemplo Art.-Nr.: 6799-2-8 DIN 6799 - 1.4122 - Ø 8mm - \*1: sin montar | \*2: montado