




Tuercas hexagonales

autoblocante con anilla de retención no metálica, forma baja



d	m	h	s	e	●
M2,5	3,5	2,3	5	5,50	5
M3	2,4	2,4	5,5	6,01	5,5
M4	2,9	2,9	7	7,66	7
M5	3,2	3,2	8	8,79	8
M6	4,0	6,0	10	11,05	10
M8	5,5	8,0	13	14,38	13
M10	6,5	10,0	17	18,90	17
M12	8,0	12,0	19	21,10	19
M14	9,5	14,0	22	24,49	22
M16	10,5	16,0	24	26,75	24
M18	13,0	18,5	27	29,56	27
M20	14,0	20,0	30	32,95	30
M22	15,0	22,0	32	35,03	32
M24	15,0	24,0	36	39,55	36
M27	17,0	27,0	41	45,20	41
M30	19,0	30,0	46	50,85	46
M33	22,0	33,0	50	55,37	50
M36	25,0	36,0	55	60,79	55

Grado	UV
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	1000
▲ ●	500
▲ ●	200
▲ ●	100
▲ ●	100
▲ ●	100
▲ ●	50
▲ ●	50
▲ ●	50
▲ ●	25
▲ ●	25
▲ ●	25
▲ ●	25
▲ ●	25
▲ ●	25

■ A1 / ▲ A2 / ● A4 | UV: Unidad de venta | Todas las medidas en mm | Otras dimensiones bajo pedido

Ejemplo Art.-Nr.: 985-2-8 DIN 985 - A2 - M8